

**Amendment and Response under 37 C.F.R. 1.116**

Applicant: Pere Obrador

Serial No.: 10/090,778

Filed: March 6, 2002

Docket No.: 10017906-1

Title: VIDEO TRANSCODER BASED JOINT VIDEO AND STILL IMAGE PIPELINE WITH STILL BURST MODE

---

**IN THE CLAIMS**

**This listing of claims will replace all prior versions, and listings, of the claims:**

1. (Previously Presented) A method for concurrently processing digital video frames and high resolution still images in burst mode, comprising:
  - acquiring regular size video frames and high resolution still image frames in burst mode from one or more image sensors;
  - downsampling the regular size video frames into reduced size video frames, wherein the reduced size frames have frame sizes smaller than the regular size video frames;
  - processing the high resolution still image frames acquired during the burst mode using a high resolution still image pipeline;
  - processing the reduced size video frames using a video pipeline, wherein the high resolution still image frames are processed concurrently with the reduced size video frames; and
  - upsampling the reduced size video frames using motion estimation and information from the high resolution still image frames.
2. (Cancelled)
3. (Currently Amended) The method of claim [2] 1, further comprising downsampling the high resolution still image frames, wherein the downsampled still image frames have same frame sizes as the upsampled video frames, and wherein blocks in the downsampled still image frames form a block pool.
4. (Original) The method of claim 3, further comprising:
  - comparing blocks in the block pool with corresponding blocks in the upsampled video frames until a best match block is found; and
  - copying the best match block into the corresponding blocks in the upsampled video frames.

**Amendment and Response under 37 C.F.R. 1.116**

Applicant: Pere Obrador

Serial No.: 10/090,778

Filed: March 6, 2002

Docket No.: 10017906-1

Title: VIDEO TRANSCODER BASED JOINT VIDEO AND STILL IMAGE PIPELINE WITH STILL BURST MODE

---

5. (Original) The method of claim 1, wherein the processing the reduced size video frames step includes encoding the reduced size video frames into a standard format by a video transcoding agent.
6. (Original) The method of claim 1, wherein the processing the high resolution still image frames step includes processing the high resolution still image frames in real time.
7. (Original) The method of claim 1, wherein the processing the high resolution still image frames step comprises:
  - downsampling and demosaicing the high resolution still image frames using complex demosaicing algorithms; and
  - color correcting the high resolution still image frames using complex color correction algorithms.
8. (Original) The method of claim 1, further comprising compressing the reduced size video frames and the high resolution still image frames.
9. (Previously Presented) A joint video and still image pipeline for a video camera system, comprising:
  - one or more image sensors capable of concurrently acquiring regular size video frames and high resolution still image frames in burst mode, wherein the regular size video frames are downsampled into reduced size video frames, wherein the reduced size frames have frame sizes smaller than the regular size video frames;
  - a sensor controller capable of storing the regular size video frames and the high resolution still image frames acquired during the burst mode into a memory; and
  - one or more processors capable of concurrently processing the reduced size video frames and the high resolution still image frames acquired during the burst mode, wherein the reduced size video frames are processed using a video pipeline, and the high resolution still image frames are processed using a high

**Amendment and Response under 37 C.F.R. 1.116**

Applicant: Pere Obrador

Serial No.: 10/090,778

Filed: March 6, 2002

Docket No.: 10017906-1

Title: VIDEO TRANSCODER BASED JOINT VIDEO AND STILL IMAGE PIPELINE WITH STILL BURST MODE

---

resolution still image pipeline, wherein the high resolution still image frames are processed concurrently with the reduced size video frames, and wherein the reduced size video frames are upsampled using motion estimation and information from the high resolution still image frames.

10. (Cancelled)

11. (Currently Amended) The joint video and still image pipeline of claim [10] 9, wherein the high resolution still image frames are downsampled to have the same frame sizes as the upsampled video frames, and wherein blocks in the downsampled still image frames form a block pool.

12. (Original) The joint video and still image pipeline of claim 11, wherein blocks in the block pool are compared with corresponding blocks in the upsampled video frames until a best match block is found, and wherein the best match block is copied into the corresponding blocks in the upsampled video frames.

13. (Original) The joint video and still image pipeline of claim 9, further comprising a video transcoding agent capable of encoding the reduced size video frames into a standard format.

14. (Original) The joint video and still image pipeline of claim 9, wherein the high resolution still image frames are processed in real time.

15. (Original) The joint video and still image pipeline of claim 9, wherein the processors are selected from a microprocessor, an application specific integrated circuit (ASIC), and a digital signal processor.

16. (Original) The joint video and still image pipeline of claim 9, wherein the processors downsample, demosaic, and color correct the high resolution still image frames using complex algorithms.

**Amendment and Response under 37 C.F.R. 1.116**

Applicant: Pere Obrador

Serial No.: 10/090,778

Filed: March 6, 2002

Docket No.: 10017906-1

Title: VIDEO TRANSCODER BASED JOINT VIDEO AND STILL IMAGE PIPELINE WITH STILL BURST MODE

---

17. (Previously Presented) A computer readable medium providing instructions for concurrently processing digital video frames and high resolution still images in burst mode, the instructions comprising:

acquiring regular size video frames and high resolution still image frames in burst mode from one or more image sensors;

downsampling the regular size video frames into reduced size video frames, wherein the reduced size frames have frame sizes smaller than the regular size video frames;

processing the high resolution still image frames acquired during the burst mode using a high resolution still image pipeline;

processing the reduced size video frames using a video pipeline, wherein the high resolution still image frames are processed concurrently with the reduced size video frames; and

upsampling the reduced size video frames using motion estimation and information from the high resolution still image frames.

18. (Cancelled)

19. (Currently Amended) The computer readable medium of claim [18] 17, further comprising instructions for downsampling the high resolution still image frames, wherein the downsampled still image frames have same frame sizes as the upsampled video frames, and wherein blocks in the downsampled still image frames form a block pool.

20. (Original) The computer readable medium of claim 19, further comprising: comparing blocks in the block pool with corresponding blocks in the upsampled video frames until a best match block is found; and copying the best match block into the corresponding blocks in the upsampled video frames.